

The Active Leak Repair Kit (ALRK) is a compression seal system designed for low-pressure, active leaks up to 75 psi. The system consists of a QuickStrap compression strap combined with a resin fiberglass outer wrap. The QuickStrap compression strap is suitable for operations handling water and harsh chemicals. The system installs rapidly, creating a compression seal - stopping the leak. The outer wrap hardens around the QuickStrap compression strap, securing it in place and protecting it from mechanical damage.

Applications

- Refineries
- Processing Plants
- Mining
- Irrigation

Storage

2 year shelf life when stored @ 75 °F. Shelf Life may be extended when stored at lower temperatures, but above 40 °F.

BENEFITS:

- Stops Active Leaks
- Seals to 75 psi
- Suitable for chemical service
- Fast and easy-to-use



MECHANICAL PROPERTIES - ELASTOMERIC STRAP

UNITS	METHOD	VALUE
Tensile Strength	ASTM D412	640 psi
Compression Set	ASTM D395B	40 %
Hardness - Shore A	ASTM D2240	60

THERMAL PROPERTIES			
ATTRIBUTE	METHOD	VALUE	
Minimum Working Temperature	-	-22° F (-30 °C)	
Maximum Working Temperature	-	176 °F (80°C)	

MECHANICAL PROPERTIES - CLADDING			
ATTRIBUTE	METHOD	VALUE	
Tensile Modulus	ASTM D638	659,206 psi	
Tensile Elongation	ASTM D638	1.2 %	
Compression Strength	ASTM D695	53,450 psi	
Compression Modulus	ASTM D695	13,755 psi	
Working Time	-	3-5 minutes	

Warranty: CSNRI routinely implements product improvements. Please contact your local distributor or office for the most current product specifications. CSNRI warrants the quality of this product when used according to directions.



Sales@cs-nri.com www.cs-nri.com

